

**In the Claims:**

1. (Previously Presented) A method of requesting operations and management data from a telephony switch at a computing device, said telephony switch and said computing device in communication with a packet switched data network distinct from a public switched telephone network, said method comprising:
  - a. establishing a connection between said computing device and said telephony switch over said packet switched data network rather than the public switched telephone network;
  - b. forming at least one packet comprising:
    - i. a network address identifying said telephony switch on said packet switched data network;
    - ii. a network address identifying said computing device;
    - iii. a first message type identifier, identifying a message contained at least partially within said packet, as a data request message;
    - iv. a second message type identifier, identifying a type of operations and management data requested from said telephony switch;
  - c. forwarding said packet from said computing device to said telephony switch using said data network.
2. (Original) The method of claim 1, wherein said packet further comprises, a security token allowing said switch to authenticate said computing device as a computing device authorized to request said operations and management data.
3. (Original) The method of claim 1, further comprising:

prior to b. exchanging login request and login reply messages between said computing device and said telephony switch, thereby establishing a message exchange session.
4. (Previously Presented) The method of claim 1, wherein said message comprises an internet protocol compliant network message.

5. (Original) The method of claim 4, wherein said connection comprises a TCP/IP connection and said at least one packet is TCP/IP compliant.
6. (Original) The method of claim 1, wherein said connection with said switch is established by way of an intermediate computing platform.
7. (Previously Presented) A method of providing operations and management data from a telephony switch to a computing device, said telephony switch and said computing device in communication with a packet switched data network distinct from a public switched telephone network, said method comprising:
- a. in response to a request from operations and management data, forming at least one packet comprising:
    - i. a network address identifying said telephony switch on said packet switched data network;
    - ii. a network address identifying said computing device;
    - iii. a first message type identifier, identifying said packet as at least partially containing a message formed in response to a request;
    - iv. a second message type identifier, identifying a type of operations and management data provided by said packet;
  - b. forwarding said packet from said telephony switch to said computing device using said data network rather than the public switched telephone network.
8. (Original) The method of claim 7, wherein said packet further comprises an alphanumeric identifier of said telephony switch.
9. (Original) The method of claim 7, wherein said packet further comprises a security token allowing said computing device to authenticate said switch as a proper switch responding to a request.
10. (Original) The method of claim 7, further comprising:

prior to a exchanging login request and login reply messages between said computing device and said telephony switch, thereby establishing a message exchange session.

11. (Currently Amended) A method of exchanging operations and management data between a telephony switch and a computing device, said telephony switch and said computing device in communication with a packet switched data network distinct from a public switched telephone network, said method comprising:

a. establishing at least first and second network connections between said computing device and said telephony switch over said packet switched data network rather than the public switched telephone network;

b. exchanging operations and management data having a first priority over said first network connection; and

c. concurrently exchanging operations and management data having a second priority over said second network connection.

12. (Original) The method of claim 11, wherein said packet switcher network adheres to the internet protocol.

13. (Previously Presented) The method of claim 11, wherein said connections are TCP/IP connections, at first and second defined logical ports at said telephony switch.

14. (Original) The method of claim 11, further comprising encapsulating operations and management messages having a pre-defined format in data packets to exchange said messages in b. and c.

15. (Previously Presented) A computer readable medium, containing computer readable instructions, that when loaded into a computing device comprising a network interface for interconnection with a packet switched data network distinct from a public switched telephone network, adapts said computing device to:

a. establish a connection with a telephony switch over said packet switched data network rather than the public switched telephone network;

b. form at least one packet comprising:

- i. a network address identifying said telephony switch on said packet switched data network;
- ii. a network address identifying said computing device;
- iii. a first message type identifier, identifying said packet as at least partially containing a data request message;
- iv. a second message type identifier, identifying a type of operations and management data requested from said telephony switch;

c. forward said at least one packet from said computing device to said telephony switch using said data network.

16. (Previously Presented) A computing device, comprising:

a processor;

a data network interface, in communication with said processor;

processor readable memory, comprising processor readable instructions, adapting said

device to:

a. establish a connection with a telephony switch over a packet switched data network distinct from a public switched telephone network with said network interface;

b. form at least one packet comprising:

- i. a network address identifying said telephony switch on said packet switched data network;
- ii. a network address identifying said computing device;
- iii. a first message type identifier, identifying said packet as at least partially containing a data request message;
- iv. a second message type identifier, identifying a type of operations and management data requested from said telephony switch;

c. forward said at least one packet from said computing device to said telephony switch using said data network interface.

17. (Previously Presented) A digital telephony switch, comprising:

a processor;  
a data network interface, in communication with said processor and connected to a packet switched data network distinct from a public switched telephone network;  
processor readable memory, comprising processor readable instructions, adapting said switch to:

- a. in response to a request for operations management data, form at least one data packet comprising:
  - i. a network address identifying said telephony switch on said packet switched data network;
  - ii. a network address identifying said computing device;
  - iii. a first message type identifier, identifying said packet as at least partially containing a message formed in response to a request;
  - iv. a second message type identifier, identifying a type of operations and management data provided by said packet;
- b. forward said packet from said telephony switch to said computing device using said data network interface.